



HDX-6 Equipment Specifications

Last Update: 08-15-16

Production Package:

2 - Grass Valley LDK 6000 Cameras with CCU & OCP Panels
Lenses are determined by client needs
2 - Vinten Heads and Tripods
Ross Synergy 1 MD 16 Channel Switcher
Leitch 16 x 16 HD Router with 4 Panels
Videotek VTM-4100 Rasterizer with Eye Pattern
Leader 5800 Scope
6 - Ross UDC8225 Up/Down/Cross Converter Frame Syncs
2 - Marshall 17" LCD PVW/PGM Monitors
15 - Marshall Dual 7" HD/SD LCD Monitors
ESE Clock
Evertz 5600MSC Test/Timecode Generator

For additional costs and upon request:

Wired for 4 Cameras
Wired for 6 Kipros
Wired for 2 - EVS 4 Channel Servers
Wired for - Chyron Duet

Transmissions:

2 - Adtec EN-81 MPEG-4/MPEG-2 HD Encoders
2 - Upcom UCT MPEG-4 IRDs
2 - MCL MT3200 350 Watt TWT Amplifiers
2 - Miteq U9696 Digital Upconverters
2 - MCL MT32 PC Phase Combiner Dual Path

Dimensions:

Height: 13' 6"
Width: 8'
Length: 32'
Power Requirements: 208 Volt, Single Phase,
150 Amp

Audio:

Allen & Heath Audio Board (16 inputs & 4 outputs)
RTS Intercom System / SAP 612 (2 Powered Channels)
2 - Studio Technologies 2 Channel IFB Systems
2 - Telos Links
2 - Gentner Telephone Couplers

